

**SAFETY DATA SHEET**  
HIGH BUILD FRICTION POLISH

Page 1

Issued: 1/1/2009

Revision No: 2

Sent to: MJM

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** HIGH BUILD FRICTION POLISH

**CAS number:** T

**Product code:** 8-60191-00012-4

**Use of substance / preparation:** Used as a sealer/polish in wood turning.

**Company name:** Doctor's Woodshop, LLC

3 Offenbach Place

Lake Oswego, OR

USA

97035

Tel: 503-522-0531

**2. HAZARDS IDENTIFICATION**

**Main hazards:** Flammable, Flash point 32 C. May be harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** BUTAN-1-OL 1-10%

EINECS: 200-751-6 CAS: 71-36-3

[-] R10; [Xn] R22; [Xi] R37/38; [Xi] R41; [-] R67

- ETHANOL 50-70% EINECS: 200-578-6 CAS: 64-17-5

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

[cont...]

**SAFETY DATA SHEET**  
HIGH BUILD FRICTION POLISH

**Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

#### 7. HANDLING AND STORAGE

**Handling requirements:** Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Hazardous ingredients:** BUTAN-1-OL  
WEL (8 hr TWA): 310 mg/m<sup>3</sup> WEL (15 min STEL): 154 mg/m<sup>3</sup>

- ETHANOL  
WEL (8 hr TWA): 1920 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**SAFETY DATA SHEET**  
HIGH BUILD FRICTION POLISH**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid  
**Colour:** Cream  
**Odour:** Perceptible odour  
**Flash point°C:** 32

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions. Stable at room temperature.  
**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.  
**Materials to avoid:** Strong oxidising agents. Strong acids.  
**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** BUTAN-1-OL  
IVN RAT LD50 310 mg/kg  
ORL MUS LD50 2680 mg/kg  
ORL RAT LD50 790 mg/kg

- ETHANOL  
IVN RAT LD50 1440 mg/kg  
ORL MUS LD50 3450 mg/kg  
ORL RAT LD50 7060 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.  
**Persistence and degradability:** Biodegradable.  
**Bioaccumulative potential:** No bioaccumulation potential.  
**Other adverse effects:** Negligible ecotoxicity.

**13. DISPOSAL CONSIDERATIONS**

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

<b>UN no:</b> 1263	<b>ADR Class:</b> 3
<b>Packing group:</b> II	<b>Classification code:</b> F1
<b>Shipping name:</b> PAINT	
<b>Labelling:</b> 3	<b>Hazard ID no:</b> 33

**SAFETY DATA SHEET**  
HIGH BUILD FRICTION POLISH**IMDG / IMO**

**UN no:** 1263 **Class:** 3  
**Packing group:** II **EmS:** F-E,S-E\*  
**Marine pollutant:** .  
**Labelling:** 3

**IATA / ICAO**

**UN no:** 1263 **Class:** 3  
**Packing group:** II  
**Packing instructions:** 305(P&CA); 307(CAO)  
**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Highly flammable.



**Risk phrases:** R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Risk phrases used in s.3:** R10: Flammable.  
R22: Harmful if swallowed.  
R37/38: Irritating to respiratory system and skin.  
R41: Risk of serious damage to eyes.  
R67: Vapours may cause drowsiness and dizziness.  
R65: Harmful: may cause lung damage if swallowed.

**SAFETY DATA SHEET**  
HIGH BUILD FRICTION POLISH

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R11: Highly flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.